



Washer Extractors TWE 10 - 15

## OPTIONS

- Dual heating (electric & steam) selectable through the control
- Stainless steel side panels
- Stainless steel back panel
- 3rd inlet valve for soft water
- Pneumatic inlet valves for faster filling
- Pneumatic steam valve
- Integrated plinth to increase loading height and ensure ergonomical operation and fit linen carts (Height 6,3 inches to reach bottom loading door of 27,6 inches)

## STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- Choice of liquid and powder detergent in 5 compartment frontal dispenser
- Standard equipped for automatic soap dosing
- Drum and tub, as well as front and top panel made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection in the front for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" drain valve for fast evacuation and shorter cycles
- Plexi double glass protection against heat
- Accelerometer for perfect balancing

MODEL	UNIT	TWE 10	TWE 15
Dry load	lb	22	35
Performance	lb/h	35	50
Cycle time	min	40-45	40-45
<b>DRUM</b>			
Drum diameter	inches	25	25
Drum depth	inches	12,6	20,5
Drum volume	cu.ft.	3,5	5,4
Wash speed	rpm	34	34
Extraction speed	rpm	1000	1000
G-Force		351	351
<b>DOOR</b>			
Door opening ø	inches	18	18
<b>HEATING</b>			
Electric	BTU	40,710	40,710
Steam	BTU	66,700	66,700
<b>ELECTRIC</b>			
Electric consumption*	HP/h	1,21	1,81
Motor	HP	2	3
<b>STEAM</b>			
Steam valve connection ø	DN-BSP	15-1/2"	15-1/2"
Steam pressure	psi	29-87	29-87
Steam consumption	lb/cycle	11	16,5
<b>AIR</b>			
Air connection ø	inches	optional / 0,31	optional / 0,31
<b>WATER</b>			
Inlet valve connection ø	DN-BSP	2 x 20-3/4"	2 x 20-3/4"
Water inlet (detergent) ø	DN-BSP	-	-
Water pressure	kPa	29-58	29-58
Water flow	gal/min	31,7	31,7
Water consumption*	cold	gal/cycle	varies
	hot	gal/cycle	varies
Drain valve connection ø (outer)	inches	3	3
Drain flow	gal/min	60	60
<b>PROGRAMMABLE CONTROL</b>			
18 default programmes (max. 99)		Std	Std
7" colour, high-resolution LCD		Std	Std
<b>DIMENSIONS</b>			
Standard WxDxH	inches	35x36x58	35x42x58
with platform 6 inches	inches	35x36x65	35x42x65
Packing WxDxH	inches	35x37x60	35x43x60
with platform	inches	35x37x67	35x43x67
<b>WEIGHT</b>			
Net	lb	914	947
Gross	lb	936	970
Net with platform	lb	981	1025
Gross with platform	lb	1003	1047
<b>SOUND LEVEL</b>			
	db(A)	62-72	62-72

\* Consumption figures based on 'Eco 60°C' program (main wash, 2 rinses)