



Washer Extractors TWE 20 - 40

STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- 4 compartment top panel dispenser :
2 for liquid and 2 for powder
- Standard equipped for automatic soap dosing
- Drum and tub, as well as front and top panel made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection in the front for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" drain valve for fast evacuation and shorter cycles
- Plexi double glass protection against heat
- Accelerometer for perfect balancing

OPTIONS

- Dual heating (electric & steam) selectable through the control
- Stainless steel side panels
- Stainless steel back panel
- 3rd inlet valve for soft water
- Pneumatic inlet valves for faster filling
- Pneumatic steam valve
- Second drain valve for water recovery

MODEL	UNIT	TWE 20	TWE 40
Dry load	lb	44	88
Performance	lb/h	66	132
Cycle time	min	40-45	40-45
DRUM			
Drum diameter	inches	27,6	35,4
Drum depth	inches	21	22,6
Drum volume	gal	7,2	13,6
Wash speed	rpm	37	35
Extraction speed	rpm	960	870
G-Force		360	366
DOOR			
Door opening ø	inches	18	18
HEATING			
Electric	BTU	61,066	81,421
Steam	BTU	66,700	66,700
ELECTRIC			
Electric consumption*	HP/h	2	3
Motor	HP	4	7
STEAM			
Steam valve connection ø	DN-BSP	15-1/2"	15-1/2"
Steam pressure	psi	29-87	29-87
Steam consumption	lb/cycle	22	44
AIR			
Air connection ø	inches	optional / 0,31	optional / 0,31
WATER			
Inlet valve connection ø	DN-BSP	2 x 20-3/4"	2 x 20-3/4"
Water inlet (detergent) ø	DN-BSP	-	-
Water pressure	psi	29-58	29-58
Water flow	gal/min	30	30
Water consumption*	cold	gal/cycle	40
	hot	gal/cycle	10
Drain valve connection ø (outer)	inches	3	3
Drain flow	gal/min	60	60
PROGRAMMABLE CONTROL			
18 default programmes (max. 99)		Std	Std
7" colour, high-resolution LCD		Std	Std
DIMENSIONS			
Standard WxDxH	inches	38x45x58	46x55x59
Packing WxDxH	inches	43x47x62	47x57x62
WEIGHT			
Net	lb	1058	1962
Gross	lb	1091	1995
SOUND LEVEL			
	db(A)	62-72	63-77

* Consumption figures based on 'Eco 60°C' program (main wash, 2 rinses)